

SPOA7-MPTWO POST PAD LIFTS

7,000 lbs. / QUICK SERVICE MOVEABLE PAD LIFTS



The quick service pad lift includes time saving features that help get your customers in and out fast with efficient, no-appointment

necessary maintenance and routine service.

Rubber spacer blocks provide clearance

Includes four (4) each 1.5" and 3" blocks

Lift pads accommodate most unibody vehicles



SPOA7-MP **MODELS**

ADJUSTABLE PAD LIFT Movable Pads (MP)

STANDARD

SPOA7N6X0BL SPOA7N6X0RD

SHOCKWAVE EQUIPPED	SPOA7U6X5BL SPOA7U6X5RD
Rise* STANDARD SHOCKWAVE	70 5/8" to 73 5/8" 73 5/8" to 76 5/8"
Overall Height	11' 8 1/2"
Overall Width	11' 5 3/8"
Drive-thru	78 1/8"
Inside Columns	107 1/4"
Pad Length Overall Retracted / Extended	71 1/8" to 87 1/4"
Min/Max Inside Distance Between Pads	39 7/8" - 56"
Min Pad Height	2 5/8"
Min Bay Size	12' X 24'
Ceiling Height Min With SHOCKWAVE	12' 12' 6"
Motor / Voltage With SHOCKWAVE	2 HP, 208-230V 5 HP / 110V
Time of Rise / Descent With SHOCKWAVE**	45 / 40 seconds 25 / 19 seconds

^{*} Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke

FEATURES:

- · 7,000 lbs. capacity models
- · 4 adjustable lift height options

MODEL SHOWN: SPOA7N6X0BL

- Available with SHOCKWAVE™ power
- · Original "Double S" column
- · ALI Gold Certified

SUPERCHARGE SPOA7 lifts with SHOCKWAVE™ SPEED

SHOCKWAVE DC powered lifts are the

fastest in the world! Boost productivity and increase service numbers.



SCAN VIDEO CODE

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA













North / South America Information

ADJUSTABLE

Sales: 800.445.5438 insidesales@rotarylift.com

Tech. Support: 800.445.5438 technicalsupport@rotarylift.com

Global Contact Information

USA: 1.812.273.1622 Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995

Government Sales: 800.445.5438 X5655

For additional information: rotarylift.com/Government-Purchasing-Assistance/



^{**} Times vary depending on vehicle weight Heights and widths reflect standard settings